

LAND MANAGEMENT

SUSTAINABLE LAND

Protecting your farm from storm damage

Main Points

- The most effective measures are pole planting to protect tracks, crossings, fencelines and dam catchments.
- Pole planting is ideal for protecting gullies and medium hill country pasture.
- Very steep or highly erosion prone-land may be more productive in forestry.

Background

In Hawke's Bay, a hill country farmer can expect an erosion event every five years and a severe erosion event every 10 years.

After a severe storm, access tracks, water supplies and fencelines need immediate and costly repair work. On a typical hill country farm with few prevention measures, damage can be expensive after a storm, eg the average cost to Wairoa District farmers after a storm similar to Cyclone Bola would be about \$35,000.

The following methods have been successfully used by farmers in Hawke's Bay to prevent damage to hill country properties. There are seven main areas on a farm susceptible to damage.

1. Farm Tracks

Damage to tracks is caused mainly by dropouts, and from debris from slips above. Surface scouring along tracks is a problem on lighter soils.

Dropouts are difficult and expensive to repair so prevention is best. Plant two to three rows of poles immediately below the track at spacings of 5-10m, with the first

row about 2m out from the track. Plant at least to the bottom of the debris from the track.



Poplar poles used to stabilise slopes above and below a farm track.

It's difficult to use trees to control debris from slips higher up hillsides blocking tracks. The most practical solution is to sweep the debris off with a blade. Obvious slump areas above the track should be planted.

Scouring can be minimised by having plenty of culverts or cutoffs.

2. Water Supplies

DAM CATCHMENTS: Protect dams from silting up if the stock water supply is dependent on dams. Identify the slopes susceptible to slipping and plant these. Also pair plant the channels as these often scour, producing large amounts of debris. Very unstable or steep slopes should be forested. Poplars and willows should not be planted on the headwall of the dam.

Following Cyclone Bola in 1988, a study showed planting poles at 10 m x 10 m spacings to stabilise the average dam catchment would cost only as much as cleaning out a completely silted up dam once.



Farm dam protected from soil erosion.

DAM SPILLWAYS: Eroding spillways have been the cause of many farm dams failing during storms. Dams with steep or large catchments have high rates of overflow which can scour spillway channels.

Spillways should be built into hard material, be of a low angle, be large enough to contain normal floods, and have a good grass cover. Willow poles can be planted on the down-hill side of the spillway to protect from drop-outs, but they need to be away from the headwall. They must also be planted a metre or more out of the spillway.

3. Gully Crossings

Protection of crossings and culverts is essential to maintain access to the farm after a flood. For each crossing plant a minimum of one pair of willows upstream and one downstream for protection. Where the crossing passes over an eroding gully, more intensive block or spaced planting will be needed, both up and downstream.

4. Fencelines

Fences are damaged during storms, both by slip debris and by drop-outs. Experience indicates that slip debris usually causes complete destruction of fences, but it is relatively easy to rebuild the fence over the debris. However, damage from drop-outs is difficult to repair without realigning the fence.

To protect fencelines, plant poles where drop outs are likely to occur. Trees should be planted on both sides of the fence at 8-10m spacings. It is often not practical to plant all the way up a slope to control all slipping, but obvious unstable areas should be planted.

5. Gullies

Watercourses are normally severely affected by heavy rain storms. This erosion affects access and begins a cycle of more erosion from the over-

steepened sides by undermining adjacent hillsides.

Control can be cost effective and simple. Willows are normally planted in pairs as close as 5m between pairs on steep country and 10-20m spacings on easier ground. Poles can be staggered down the water course where erosion is less severe.

Poles should be planted just out of the normal flood level on good soil, but away from the top edge of high, vertical eroded gully sides.

6. Streams and Rivers

Stream bank erosion is more difficult to control than gully erosion. Preventative work should be undertaken such as planting poles on the outside of bends and shrub willow planting in areas which are beginning to erode. Major work such as groyne construction should be done only with the assistance of a river engineer.

7. Protecting Hill Country Pasture

Although slips grass over quickly, pasture growth only reaches 70-80% of the uneroded production after 30 years. Most of this recovery is within the first 10 years. Trials in Gisborne showed poplars planted 11 x 11 metres apart reduced the risk of slipping by more than 80%.

Pasture can be protected from storm damage by planting poles at 10-15m spacings and greater, depending on the site. Timber production from these trees is also a possibility. Sites needing protective planting can often be identified from old slip scars. These and surrounding areas need planting.

Erodible hill slope protected from slipping with Matsudana Willows. These can also be used for fodder.



For further information

For information on sustainable land management, ask for the other titles in this series, or contact Land Management staff at Hawke's Bay Regional Council for advice.

Wairoa	0-6-838 8527
Guppy Road, Napier	0-6-844 2495
Waipukurau	0-6-858 8636
TOLL FREE	0800 108 808